

Jeep Assembly Instructions

(Use Parts List to Identify the Parts)

Preparation

- a) The Jeep is assembled by number, i.e. like numbers will press fit together; #2 goes with the #2 on another part. No tools are required although a small hammer will be helpful for wheel assembly. The model can be assembled with or without glue. If glue is used it is recommended that the parts be dry assemble to insure proper fit gluing.
- b) The pieces are cut from 1/8 Birch Plywood. Occasionally in humid conditions wooden parts may swell slightly. If swelling occurs or if parts do not fit together easily, sand lightly with 180 grit sandpaper to fit.
- c) Some parts have arrows to indicate correct orientation.
- d) Start by laying out all parts engraving side up, using the parts list as a guide. Separate the parts into groups:

Wheel & Axle Assembly

- a) The five tire assemblies are made up of 3 pieces each held together with 2 small lugs which are pressed into the 2 slots in each part.
- b) To Assembly hold the 2 tires and the wheel together (wheel in middle) line up the slots in the tread and press a lug into the slot as far as you can by hand. Insert the second lug in the same manner. To seat the lugs, keep the assembly together and firmly press the lugs against a hard surface or gently tapped them with a hammer. Repeat this for the remaining 4 tire & wheel assemblies.
- c) Add the tires to axels and secure each with a round locking tab.

Roof Assembly

- a) Press the roof rails (ref 26 & 27) into the roof.

Jeep Assembly

- a) Insert the floor board (ref 1, 2) into the slots in the left and right frames and push forward to lock into the frame and install the front and rear wheel assemblies into the corresponding slots in the frame (ref 38, 39, 40, 41).
- b) Press the front and rear bumpers (ref 3 & 4, 5 & 6) into the frame assembly.
- c) Add the rear seats, seat bottom, steering wheel and windshield (ref 7 & 8, 9 & 10, 11, 12 & 13) into the frame assembly.
- d) Install the rear deck (ref 18 & 19) and the front deck and hood (ref 28, 29 & 30). Lock the hood and deck with the lock (ref 30 & 31).
- e) Install the left and right body panels into the slots on the floor and behind the side mirrors. Lock the body panels in place with the right and left trim pieces (ref 16 & 17) and secure them under the floor with square locking tabs.
- f) Install the rear top and bottom body panels (ref 20, 25),
- g) Install the grill / head lights and grill guard into the slots in the front frame..
- h) Install the roof assembly and the spare tire. Secure the tire with a lock.